



ROTAX® ENGINE	850 E-TEC	850 E-TEC Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2	2
Displacement	849 cc	849 cc
Bore	82 mm	82 mm
Stroke	80.4 mm	80.4 mm
Maximum engine speed	7900 RPM	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3,4 liters	

COLOUR	Bright White / Viper Red	
DIMENSIONS		
Vehicle overall length*	3130 mm (3700) 3230 mm (3900)	
Vehicle overall width	1120 mm	
Vehicle overall height	1280 mm	
Ski stance	921 mm	
Track nominal width	381 mm	
Track nominal length	3705 mm 3912 mm	
Track profile height	64 mm PowderMax / Light 76 mm PowderMax Light Large (spring only, 3900)	

POWERTRAIN

Drive clutch type	pDrive with clickers	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line adjustable brake lever, plastic master cylinde with protector	

SUSPENSION

Front suspension	LFS	
Front shock	KYB 36 CR Kashima	
Rear suspension	PPS ² -DS+-3700 PPS ² -DS+-3900	
Center shock	KYB 46 HLCR Kashima	
Rear shock	KYB 46 HLCR Kashima	

FEATURES

Frame	Radien²	
Skis	Blade DS+	
Seating	Shredder DS, 1-up	
Handlebar	U-type aluminium with hooks, low grab handle	
Riser block height	145 mm	
Starter	Manual with SHOT	

Reverse	RER	
Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	4.5-in. digital display 10.25-in Color Display with BRP Connect (spring only)	
USB power outlet	Yes, in front compartment	
LinQ attachment	2 pairs	



 $^{^{\}ast}$ Vehicle overall length without snowflap.